

EVE E-160ZQ

- Full-color ellipsoidal designed for mobile and installation applications
- Integrated zoom optics ensure subject remains in the spotlight from a wide range of distances
- Pre-set color temperature ranges eliminate the need for manual color blending
- Flicker-free operation suitable for on-camera use
- D-Fi USB compatibility for wireless master/slave or DMX control
- powerCON®-compatible power input/output connections for power linking



Specifications

- DMX Channels: 3, 4, 11
- DMX Connectors: 3- and 5-pin XLR
- Gobo Size: M (66 mm outside, 48 mm image, 2 mm max thickness)
- Accessory Holder Size: 6.25 in
- Light Source: 1 LED (quad-color RGBW) 160 W, (7.3 A), 50,000 hours life expectancy
- Color Temperature Range: 2800 K – 8000 K
- Strobe Rate: 1 to 30 Hz
- Zoom Angle (manual): 24° to 37°
- Illuminance (24°): 7072 lux @ 2 m
- Illuminance (37°): 2964 lux @ 2 m
- Illuminance (24°): 1132 lux @ 5 m
- Illuminance (37°): 474 lux @ 5 m
- Lumens: 5231
- CRI: 96
- Power Linking: 9 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 150 W, 1.3A @ 120 V, 60 Hz
- Power and Current: 150 W, 0.7 A @ 230 V, 50 Hz
- Weight: 12.2 lb. (5.5 kg)
- Size: 18.4 x 9.8 x 16.9 in (467 x 248 x 429 mm)
- Approvals: CE, RoHS, UKCA, MET

