

Shocker Panel FX

- **Update:** 3-pin and 5-pin DMX connectors.
- Versatile blinder, wash and strobe light with brilliant eye candy effects
- 16 controllable sections (8 RGB + 8 white) allows for creative programming flexibility
- Rugged, all-metal housing makes it ideal for mobile applications
- Trigger eye-catching built-in macros via the display or DMX
- powerCON®-compatible power input/output connections for power linking
- Easily transports in the optional CHS-25 VIP gear bag



Specifications

- DMX Channels: 4, 7, 18, 34 or 47
- DMX Connectors: 3- and 5-pin XLR
- Light Source: 480 LEDs (tri-color) 2 W, (1 A), 50,000 hours life expectancy
- Light Source: 32 LEDs (cool white) 1.1 W (0.4 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 119°
- Field Angle: 158°
- Illuminance: 1,131 lux @ 2 m
- Lumens: 13,626
- Power Linking: 5 units @ 120 V; 10 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 296 W, 2.5 A @ 120 V, 60 Hz
- Power and Current: 281 W, 1.3 A @ 230 V, 50 Hz
- Weight: 8.6 lb (3.9 kg)
- Size: 12.63 x 4.3 x 6.7 in (310 x 110 x 170 mm)
- Approvals: CE, UKCA , ROHS

