

# GENERATION LIGHTING

## 96118S-32: 12V Clear T3 Festoon 3000K LED Lamp



**Collections:** Lx LED Festoons (Primary)  
Lx Components

Upgrade to our Lx LED Festoons from our 5w Xenon Festoons and realize an energy savings of over 80% without compromising light output. Lx LED Festoons are dimmable on magnetic and electronic low voltage systems. For magnetic systems, a standard incandescent or magnetic low voltage (MLV) dimmer can be used. For electronic, an electronic low voltage (ELV) dimmer is recommended.

Applications: Task & accent lighting for undercabinet, coves, toe-kick spaces and so much more. Directional nature of LED is ideal for in-cabinet lighting.

Retrofit/Remodel Installations for Magnetic Transformer Systems - JUST REPLACE THE LAMP! Compatible as a retrofit for existing Lx Xenon lamp and compatible Xenon lamp systems. Note: The unique design of the PCB (Printed Circuit Board) makes over voltage due to under capacity a non-issue.

Product Features: Ease of installation. Ease of retrofit/remodel. Bendable/flexibility of the system.

Dimmability: Dimmable with standard incandescent dimming switch.

A "Fit & Forget" Solution: Offering 35,000 hours of useful life (equivalent to 30 years at 20 hours of use per week)

Efficacy: 85 Lumens/Watt

LED Festoon Product Line Options & Features: Warm (3000K) and Warmer (2700K) CCT; Clear lens for optimal performance; Frosted lens to reduce glare; 3 Year Warranty

UPC #:785652028045

## Dimensions:

**Diameter:** 15/32"  
**Length:** 1 5/8"

**Bulb Appearance:** Frosted -  
Glass Lens

**Bulb Type:** T3

**Bulb Base:** Festoon

**Volts:** 12

**Watts:** 0.6593

**Watts Consumed:** 0.6593

**Watts Rated:** 0.6593

**Hours Rated:** 50000

**Lumens:** 60

**Bulb Temp:** 3000 °K

**CRI:** 80

## Features:

- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

## Material List:

## Safety Listing:

Safety Listed for Damp Locations  
Safety Listed for Damp Locations

## Instruction Sheets:

Trilingual Lyte (English, Spanish, French) (HC-1715FS)

## Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	96118S-32	1	785652028045	2	2	0.75	0.002	0.001	85	Yes
Master Pack	96118S-32	500	10785652028042	13.25	11	12.5	1.054	12.7	85	Yes
Shipping Master	96118S-32	500	20785652028049							

NJ Pallet		25000		48	40	67.5	75	635		No
NV Pallet		25000		48	40	67.5	75	635		No