

PROJECT NAME: _____
 NOTES: _____

CAT. #: _____
 FIXTURE SCHEDULE: _____

BA10 LED CLEAR/FROSTED FILAMENT LAMP Filament Series



EF3.5BA10D9xx/JA8



EFF3.5BA10D9xx/JA8

Product Description:

MaxLite's LED filament lamps reproduce the elegant ambient effect of incandescent bulbs for hospitality, restaurant, residential, and retail applications. Available with both clear and frosted glass, these dimmable candelabra lamps lend a decorative touch and long-lasting illumination to wall sconces and chandeliers.

Features:

- Wattage: 3.5W
- Lumens: 315lm to 600lm
- Efficacy (lm/W): 90lm/W to 100lm/W
- Suitable for Wet Locations and for use in Enclosed Luminaires

Applications:

- Pendants
- Decorative lighting fixtures

Dimensions

MODEL NUMBER	L	D
EFx3.5BA10D9xx/JA8	3.6 inches	1.4 inches



Ordering Information

FAMILY	WATTAGE	SHAPE	DIMMABILITY	COLOR TEMPERATURE & JA8 LISTING
EF= Enclosed Clear Filament EFF= Enclosed Frosted Filament	3.5= 3.5W	BA10= BA10 Shape	D= Dimmable	927/JA81= 90 CRI, 2700K, JA8 Gen 1 930/JA81= 90 CRI, 3000K, JA8 Gen 1

Stocked Items

ORDER CODE	MODEL NUMBER	QTY IN CASE
112473	EF3.5BA10D927/JA8	50
112474	EF3.5BA10D930/JA8	
112475	EFF3.5BA10D927/JA8	
112476	EFF3.5BA10D930/JA8	



3-year standard warranty (further details available at www.maxlite.com/warranties)

BA10 LED CLEAR/FROSTED FILAMENT LAMP

Filament Series

Specifications	EF3.5BA10D9xx/JA81	EFF3.5BA10D9xx/JA81
Shape, Base	BA10, E26	
Replacement Wattage	40W Inc.	
Input Wattage (W)	3.5W	
Lumens Delivered (lm)	320	
Nominal Efficacy (lm/W)	≥90	
CCT	2700K, 3000K	
CRI	≥90	
Distribution	320°	
L70 Lumen Maintenance	15,000 Hrs	
Dimming Technology	Triac - Forward Phase Cut	
Dimming Range	10-100%	
Input Voltage	120V AC, 60Hz	
Surge Protection	2.5kV Ringing Wave	
Power Factor	≥0.9	
Diffuser	Clear Glass	Frosted Glass
Operating Temperature	-4°F to 104°F (-20°C to 40°C)	
Environment	Suitable for Wet Locations and for use in Enclosed Luminaires	
Certifications	cETLus listed, RoHS Compliant, FCC, T20, JA8-2022-E	
Warranty	3 years	

Dimming Compatibility

MANUFACTURER	MODELS
Lutron	DVCL-153PR-GR, DVCL-153PR-GR, MSCL-OP153MH-WH, RCL-153PNLH-WH, TGCL-153PR-WH
Leviton	C22-6672-1CW

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.