



# BASELITE – GH – INC – SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	/	/	/	/	/	/	/	X	/
EXAMPLE:	A GH12	B 41	C E16	D CB ½"	E 43	F 45W	G 3K	H LDM120	I PR3	J -	K 44	

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



GH20/74/ST18/STC/74/150INC/AH3

## A - SHADES

### GH SERIES

- GH12** - 100W INC (MAX), (3" GLASS), (3" GUARD)
- GH14** - 100W INC (MAX), (3" GLASS), (3" GUARD)
- GH16** - 100W INC (MAX), (3" GLASS), (3" GUARD)
- GH18** - 100W INC (MAX), (4" GLASS), (4" GUARD)
- GH20** - 100W INC (MAX), (4" GLASS), (4" GUARD)

## B - FINISH OPTIONS

(\*SEE NOTES FOR LIMITATIONS\*)

(SEE WEBSITE FOR SWATCH COLORS)

- 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
- 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60, 61,
- 62, 63, 70, 71, 72, 73

## C - MOUNTING OPTIONS

### ½" ARM EXTENSIONS

- E1, E3, E4, B1, E16, E17

### ¾" ARM EXTENSIONS

- E3A, E4A, E5, E6, E7, E8, E9,
- E10, E11, E12, E13, B15, B15S,
- E19, E20, E21, E25

### E14 - CREATE YOUR OWN

(BASELITE WILL TAKE YOUR SKETCH AND FABRICATE A CUSTOM ARM EXTENSION TO MEET YOUR NEEDS).

### CORD MOUNT

- BLC, WHC, TCB, TCW, TCHB, TCHW, TLB,
- TLW, TLB, TLW, RCB, RCW, RCHB, RCHW,
- FHB, FHW, CBLC, CWHC, CHB, CHW

### STEM MOUNT

- DP24, ST6, ST12, ST18, ST24, ST36, ST48,
- STXX

## D - MOUNTING ADD-ONS

### INC ADD-ONS

- CB1/2", CB3/4", CBC1/2", CBC3/4", SLC1/2"
- SLC3/4" STC1/2"

### UNIVERSAL ADD-ONS

- FH ½", FH ¾", LGSWL

## E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## F - LIGHT SOURCE

(SEE PAGE 4 FOR WATTAGE LIMITATIONS)

- INCANDESCENT (INC)**
- 100W

## G - LED COLOR TEMP

NOT AVAILABLE

## H - ELECTRICAL OPTION

NOT AVAILABLE

## I - GLASS OPTIONS

### 3" GLASS (AVAILABLE FOR GH12, GH14, GH16)

- CL3, CLT3, BL3, RE3, GR3,
- AH3, FR3, FRT3, PR3

### 4" GLASS (AVAILABLE FOR GH18, GH20)

- CL4, CLT4, BL4, RE4, GR4,
- AH4, FR4, FRT4, PR4

## J - ACCESSORIES

### 3" GUARDS (AVAILABLE FOR GH12, GH14, GH16)

- CG1, WG1

### 4" GUARDS (AVAILABLE FOR GH18, GH20)


- CG2, WG2

## K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## NOTES

- FINISH OPTIONS 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
  - FINISH OPTIONS 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
  - FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
  - FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
  - COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- \*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
  - \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
  - \*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
  - \*FIXTURE DIMENSIONS MAY VARY ± 0.25.
  - \*CORD AND CANOPY COME IN THE SAME COLOR.
  - \*RATED FOR WET LOCATION.




<b>GH12</b>	H - 9.875"	W - 12"
<b>GH14</b>	H - 9.875"	W - 14"
<b>GH16</b>	H - 9.875"	W - 16"
<b>GH18</b>	H - 11.5"	W - 18"
<b>GH20</b>	H - 11.5"	W - 20"



**C - MOUNTING OPTIONS**


**1/2" ARM EXTENSIONS**

\*ARMS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED




**3/4" ARM EXTENSIONS**

\*ARMS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED



**STEM MOUNTS**

\*STEMS RATED FOR DAMP LOCATION



**DP24** DOUBLE PENDANT 20"(H) 24"(W)

\*DP24 COMES STANDARD WITH STC AND ST18



**ST(XX)** STEM- 1/2" NPT

XX = LENGTH OF STEM

(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)

\*CANOPY NOT INCLUDED, ADD IN SECTION D

\* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST





**F – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) <small>MED E26</small>					
<b>INC 100W</b> - GH12, GH14, GH16, GH18, GH20			<p><b>*IMPORTANT</b> – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.</p> <p>EXAMPLE: / INC100W /</p>		
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A

**I – GLASS OPTIONS**

\*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.  
\*3" GLASS AVAILIABLE FOR GH12, GH14, GH16      \*4" GLASS AVAILIABLE FOR GH18, GH20



- CL3** 3" CLEAR GLASS
- CL4** 4" CLEAR GLASS
- CLT3** 3" CLEAR TEMPERED
- CLT4** 4" CLEAR TEMPERED



- PR3** 3" PRISMATIC GLASS
- PR4** 4" PRISMATIC GLASS



- RE3** 3" RED GLASS
- RE4** 4" RED GLASS



- BL3** 3" BLUE GLASS
- BL4** 4" BLUE GLASS



- FR3** 3" FROSTED GLASS
- FR4** 4" FROSTED GLASS
- FRT3** 3" FROSTED TEMPERED
- FRT4** 4" FROSTED TEMPERED




- AH3** 3" AMBER HYDE GLASS
- AH4** 4" AMBER HYDE GLASS



- GR3** 3" GREEN GLASS
- GR4** 4" GREEN GLASS

GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"


GLASS – MAX WATTAGE	
3" GLASS – 100W INC / LED12W	




**J – ACCESSORIES**

\* 3" GUARDS AVAILIABLE FOR GH12, GH14, GH16


\*4" GUARDS AVAILIABLE FOR GH18, GH20




**WG1** WIRE GUARD



**WG2** WIRE GUARD



**CG1** CAST GUARD



**CG2** CAST GUARD